

# Model# LRG3601U

## Thor Kitchen 36-inch Professional Gas Range



### DIMENSION & WEIGHT

#### Product Dimension

Product width	36"
Product height (from bottom to top of back splash)	36.29"-37.29"
Product height (from bottom to top of side panel)	35.6"-36.6"
Product depth (from back panel to bullnose)	28.31"
Product depth (from back panel to control board)	27.04"
Product depth (from back panel to side panel front)	24.77"
Depth of control panel (minimum)	2.27"
Depth of control panel (bullnose)	3.54"
Adjustable legs	not to exceed 1"
<b>Required Cutout Size (W x D x H) (in)</b>	<b>36 1/8" x 24.77" x 35.6(+1)"</b>

### FEATURES

Black Porcelain Drip Pan for Easy Surface Cleaning  
Heavy Duty Continuous Cast Iron Cooking Grates  
Black ABS Knobs  
6.0 cu.ft Oven Capacity  
Gray Porcelain Oven Interior with White Flakes  
One Halogen Lights  
Commercial Convection Fan  
Three Layers Glass Window  
Storage Drawer at Bottom

9K	12K	9K
18K	12K	18K

### BURNER PERFORMANCE



Total Number of Range Top Burners	6 Burners
Front Right (Single)	18,000 BTU
Front Left (Single)	18,000 BTU
Front Middle (Single)	12,000 BTU
Rear Right (Single)	9,000 BTU
Rear Left (Single)	9,000 BTU
Rear Middle (Single)	12,000 BTU
Tube Broil burner	10,000 BTU
U-shape burner (30" Oven)	18,500 BTU

### TECHNICAL DETAILS


Fuel Type	Natural Gas / LP Convertible
Electrical Requirements	120V
Circuit Breaker (A)	15 or 20 A
Frequency (Hz)	60 Hz

### ACCESSORIES (NOT INCLUDED)

LPKLRG3601U	Liquid Propane Gas Conversion Kit
RG1022	Cast Iron Reversible Griddle



**NG: Input Pressure: 7 inches,  
Output Pressure: 5 inches  
LP: Input Pressure: 11 inches  
Output Pressure: 10 inches  
Size of Regulator: ½ inch**



LRG3601U