


116 HOOK COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



99 Hour
Timer



30-90°
Precision
Thermostats



Glass
Observation
Window



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

116RCUDG SPECIFICATIONS

Max Power Usage	4 kW (2 kW x 2 Zones)	Total Tray Area	N/A
Avg Power Usage	1.6 kW (800 W x 2 Zones)	Total Trays	116
Voltage / Frequency	200-240V/50-60Hz	Tray Dimensions	N/A
Max Amperage	16A	Space Between Trays	N/A
Safety Breaker Required	Single Phase/25A	Tray Mesh Spacing	N/A
Temperature Range	Ambient Mode, 85 - 195°F	Machine Weight	108 lbs
Timer	0 - 99hr	Product Dimensions (W x H x D)	23.3" x 5' 8.7" x 18.9"
Independent Zones	2	Features	Memory Function, Ambient Air Mode
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminum door handle; Tempered glass observation window; Control Panel with PVC finish.		