

SEMI-FLUSH FIXTURE INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them a later date.

CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C) standards. If you are unfamiliar with proper electrical wiring connections, obtain the services of a qualified electrician. Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

1. Attach the Cross Bar to the Outlet Box by the mounting Screw.
 2. Make wire connections:
 - White Wire from fixture to White Wire from power source.
 - Black Wire from fixture to Black Wire from power source.
 - Loop the Ground Wire to Cross Bar with a Green Screw
 3. Attach the Back Plate against the Cross Bar and screws with the Ball Nut.
 4. Attach the arm onto the banding, then screw with the ball nut-2 and ball nut-3.
 5. Thread the nipple-2 into the coupling with hex nut-1. Attached the tube-3, cover-4 and cover-5, then screw with the hex nut.
 6. Put the Glass-7 into the Nipple-2, attached the plastic washer-8 and metal washer-9, then screw with the Hex nut-10.
 7. Attached the Cover-11, then screw with the Finial-12.
- INSTALLATION IS NOW COMPLETED.

