




Parts:



Replacement Parts:




Cartridge: KSRP3891C



Handle: LSH8771CTL

KINGSTON

GOURMETIER



CARE AND MAINTENANCE OF YOUR FAUCET

Your KINGSTON faucet has been finished to the most strict standards; however, due to the high content of minerals in the water, your finish may appear dull and tarnished after time. These are some do's and don'ts to maintain the luster on your faucet for many years to come.

DO

1. Use a silicone based caulking when installing.
2. Clean your faucet with only a mild soap and water solution.
3. Dry your faucet after using it.
4. Give it a coat of Carnuba Wax periodically.




DON'T

1. Use plumbers putty when installing the faucet.
2. Use any abrasive cleaning agents.

It may seem like a very simple and short list but it is that simple to maintain your faucet, looking shiny and new.

If your faucet is already looking somewhat dull and tarnished, before replacing it, try cleaning it with a 50/50 solution of vinegar and water, you may need to soak some rags and wrap around those stubborn areas, leave overnight and rinse completely in the morning, apply Carnuba wax once you have removed the mineral deposits.

Parts:

Washer & Lock Nut	Support	Cone Washer & Coupling Nut
		
1Pc	1Pc	2 Pcs

www.kingstonbrass.com

TOLL-FREE CUSTOMER SERVICE: 1-877-2-KBRASS
TECHNICAL SUPPORT E-mail: service@kingstonbrass.com
12775 Reservoir Street, Chino, CA 91710

NOTICE

Failure to follow all directions may cause leaks which may result in water damage


GOURMETIER

Single Handle Pull-Down Kitchen Faucet Installation Instructions

BEFORE BEGINNING INSTALLATION:


1. Flush plumbing lines to clear any debris.
2. Shut off both supply lines after flushing.

1




1. Shut off hot and cold water supply under sink. Plug sink drain with cloth to avoid losing small parts. Remove old faucet.

3




3. Carefully place the support, washers and lock nut into faucet shank and secure them gently, make sure faucet is in center position.

2




2. Place optional escutcheon or flange on bottom of new faucet before position faucet through mounting hole.

4




4. Apply Teflon tape to inlet shanks and connect supply lines.

Tools Required




Basin Wrench




Adjustable Wrench



Teflon Tape




Silicone Sealant




Screwdriver

5




5. Apply Teflon tape to threads on faucet shank and shut off valves, connect water supply line.

6




6. Turn on water supply valves and check for leaks, especially all supply line connections.

7



7. Remove the spray head and, while holding the hose over the drain, turn on the faucet for at least one minute. This will help clear the line of any debris. Be sure to check for leaks during this process.

8



8. Insert washer and attach spray head, insert spray head onto faucet body.

Warning!!!

- Do not over-tighten nut during installation.
- Over-tighten may crack the valve and cause severe leak.