

INSTALLATION AND SAFETY INSTRUCTIONS

FOR YOUR SAFETY

WARNING: BE SURE THE ELECTRICITY TO THE WIRES YOU ARE WORKING ON IS SHUT OFF; EITHER THE FUSE IS REMOVED OR THE CIRCUIT BREAKER IS SHUT OFF.

GENERAL

You don't need special tools to install this fixture.

Be sure to follow the steps in the order given. Under no circumstances should a fixture be hung on house electrical wires, nor should a swag type fixture be installed on a ceiling, which contains a radiant type heating system. Read instructions carefully. If you are unclear as to how to proceed, consult a qualified electrician.

NOTE: Proper wiring is essential for the safe operation of this fixture.

FIXTURE ASSEMBLY

Carefully removed the fixture from the carton and check that all parts are included as shown in figure. Be careful not to misplace any of the screws or parts, which are needed to install this fixture.

INSTALLATION

STEP 1: Assemble the loop(I) onto the top nipple of the fixture (J) and screw it tightly.

STEP 2: Determine the length of chain required to hang the fixture at the desired height. Using quick link attach to the top loop (I) of the fixture. Lace fixture wire and ground wire up through every other link of chain.

STEP 3: Attach the mounting strap with screw collar loop(E) onto the outlet box (A) by using two mounting screws(D), secure canopy under ceiling with screw collar ring

STEP 4: Fasten the end link of chain to the screw collar loop, slide the screw collar ring and the canopy down onto the fixture, Insert the fixture wire and the ground wire up through the nipple to outlet box (A).

STEP 5: Pull out the source wires from the outlet box(A).

Make wire connections using wire nuts(B) as follow:

--Connect the smooth-coated wire(marked) from the fixture to the black wire from the power source.

--Connect the ribbed-coated wire(unmarked) from the fixture to the white wire from the power source.

--Attach the fixture grounding wire(usually green insulation or bare wire) to the mounting strap with the green ground screw(C), and then connect it to the house grounding wire with wire nut(B).

Carefully tuck the connected wires back into the outlet box.

STEP 6: Next raise the canopy to the ceiling and secure in place by screwing the screw collar ring onto the screw collar loop (E)

STEP 7: Put the glass shade (L) to the socket cup and use the socket ring (L) to tighten it.

STEP 8: Install a bulb(Not included).Check re-lamping label at socket area or packaging for maximum allowed wattage.

CLEANING

To clean, wipe fixture with a soft and dry cloth. Do not use abrasive materials such as scouring pads or powders, steel wool or abrasive paper.

Line art shown may not exactly match the fixture enclosed. However, the installations do apply to this fixture.

