

# KOHLER®

## Roughing-In

### K-1139-H, K-1139-LH, K-1139-RH PROFLEX® 6036 WHIRLPOOL BATH WITH HEATER

#### Product Information

Applicable products:	
Whirlpool bath with heater - drop-in (shown)	K-1139-H
Whirlpool bath with heater - left drain hole, tile flange	K-1139-LH
Whirlpool bath with heater - right drain hole, tile flange	K-1139-RH

Fixture*:	
Bathing well:	
Basin area, bottom	46" (1168 mm) x 15" (381 mm)
Basin area, top	55" (1397 mm) x 25" (635 mm)
Weight	60 lbs (27.2 kg)
To overflow:	
Water depth	14" (356 mm)
Capacity	57 gal (215.8 L)
* Approximate measurements for comparison only.	

Drop-in cutout	58-1/2" (1486 mm) x 34-1/2" (876 mm)
----------------	--------------------------------------

Pump:	V	Hz	A
1-speed	120	60	7.5

Heater:	kW	V	Hz	A
	1.5	120	60	12.5

#### Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (610 mm) of the pump.	

#### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 37 lbs/square foot (183 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

