

## **THANK YOU FOR YOUR PURCHASE!**

*DO NOT APPLY IN COLD WEATHER (BELOW 50 DEGREES) VINYL BECOMES BRITTLE  
DO NOT APPLY IN EXTREME HEAT (ABOVE 90 DEGREES)  
VINYL BECOMES SOFT AND STRETCHY  
DO NOT USE RUBBING ALCOHOL TO APPLY IT DESTROYS THE ADHESIVE  
DO NOT TOUCH THE ADHESIVE BACKING OF THE DECAL  
DO NOT BE ALARMED IF YOUR DECAL CAME IN TWO PARTS.  
IN MANY CASES THE DECAL IS EASIER TO MANAGE WHEN IT NOT SO BIG*

## **HOW TO APPLY**

### **1. CLEAN:**

*WIPE THE SURFACE YOU ARE APPLYING THE DECAL  
TO WITH A DAMP CLOTH (WATER ONLY). DRY BEFORE APPLYING .*

### **2. MEASURE AND LEVEL:**

*DETERMINE THE DESIRED LOCATION AND MEASURE FOR  
PLACEMENT USING A LEVEL. MAKE SURE THE DECAL IS  
LEVEL AND POSITIONED SYMMETRICALLY.*

### **3. SECURE WITH TAPE:**

*WHILE STILL HOLDING THE LEVELED POSITION, PLACE A FEW  
PIECES OF TAPE AT THE TOP OF YOUR DECAL.*

### **4. TAPE IN PLACE:**

*APPLY ANOTHER PIECE OF TAPE (HORIZONTALLY) ACROSS THE TOP  
OF THE VINYL GRAPHIC.*

### **5. REMOVE BACKING PAPER:**

*WITH THE TAPE FUNCTIONING AS A HINGE, FLIP THE VINYL  
OVER AND CAREFULLY REMOVE THE BACKING PAPER FROM  
THE GRAPHIC.*

### **6. APPLY THE GRAPHIC**

*SLOWLY LOWER THE GRAPHIC IN PLACE APPLYING  
PRESSURE USING A CREDIT CARD. WORKING FROM THE  
CENTER OF THE GRAPHIC TO THE EDGE.*

### **7. REMOVE TRANSFER TAPE**

*CAREFULLY AND SLOWLY PEEL AWAY THE TRANSFER TAPE AT  
A 45 DEGREE DOWNWARD ANGLE.*

## **DECAL REMOVAL**

*GO OVER THE DECAL AREA WITH A BLOW DRYER ON LOW HEAT  
FOR APPROXIMATELY 30 60 SECONDS. THIS SOFTENS THE ADHESIVE BACKING  
ON THE DECAL AND MAKES IT PLYABLE AND EASY TO REMOVE*