



PRODUCT DESCRIPTION

Multiple mid-powered LEDs illuminate the acrylic diffuser uniformly without socket shadows which are common in conventional flush mounts.

FEATURES

- Energy Star® rated
- Wet Location Listed
- CEC Title 24 Compliant
- CSA listed
- ADA compliant
- Wall or Ceiling Mount
- Opaque acrylic diffuser
- Multiple LED array for uniform illumination
- 120VAC - no driver needed
- Smooth and continuous ELV dimming
- 36,000 hour rated life
- 5 year warranty

SPECIFICATIONS

Construction: Steel with white acrylic diffuser

Input: 120VAC

ELV Dimming: 100% - 10% Electronic Low Voltage

Harmonic Distortion (THD): 16% for Input Current at 120VAC

Operating Temperature: -35°C (-31°F) to 50°C (122°F)

ORDERING NUMBER

	Watt	Mounting	Color Temp	CRI	LED Lumens	Delivered Lumens	Finish
	FM-304 12W	Retrofit over a 4" recessed can or install over a junction box	930 3000K	90	670	570	BN Brushed nickel BZ Bronze WT White
	FM-306 15W	Retrofit over a 5" or 6" recessed can or install over a junction box	930 3000K 940 4000K	90	1110 1165	865 905	BN Brushed nickel BZ Bronze WT White
	FM-306 15W	Install over a junction box only	930JB 3000K	90	1110	865	WT White

FM-30 _____ - _____ - _____