roject:	
ixture Type:	
ocation:	
ontact:	

LED SQUARE

Ceiling mounted • Damp location listed





Description:

A tapered, square, linen finish glass diffuser is paired with an energy-efficient, high-performance LED source in this contemporary ceiling fixture.

Specifications:

- Brushed Nickel (-009) (plated)
- · Steel construction
- · Etched White Linen diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- covers a standard 4" octagonal recessed outlet box
- · Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	25w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1770/70 (LM-79)
ССТ	3000 K
CRI	90+
Life (hours)	50,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	
Max. Operating Temp	30° C
Warranty	
Labels	cCSAus Damp location listed
	ENERGY STAR® qualified
	Meets California Title 24 high efficacy
	requirements for outdoor use

Images:



Dimensions:

Diameter: 11-1/2" Height: 4-7/8"