



## General Information

Type	pedestal light
Product segment	Outdoor
Theme	sonstige / nicht zuordenbar
FSC®	FSC® Mix70% Pinus rad. FSC® C152762

## Dimensions

Article Height (in mm)	340
Article Width (in mm)	60
Article Length (in mm)	110
Net Weight (in kg)	1 Kilogram
Article Diameter (in mm)	165
Base Diameter (in mm)	115
Article Overhang (in mm)	95
Canopy Height (in mm)	24
Canopy Diameter (in mm)	105
Canopy Length (in mm)	710
Canopy Width (in mm)	48
długość podstawy(w mm)	70
Szerokość podstawy (w mm)	70
Installation Depth (in mm)	115
Cutout (in mm)	79

## Material & Colour

Enclosure Material	cast aluminium
Enclosure Colour	black
Glass/Shade Material	plastic
Glass/Shade Colour	white
Cable Colour	transparent

## Functionality

Switch Type	without switch
Battery	No
Function	LED not replaceable
Sensor Angle (in °)	120
Sensitivity min. (in lux)	2
Sensitivity max. (in lux)	300
Burning Time min. (in sec.)	10
Burning Time max. (in sec.)	480
Distance (in Meter)	6
Battery Type	AAA; R03P; 1,5V

## Technical Information

Protection Degree	IP54
Protection Class	1
Mains Voltage	220-240V,50/60Hz
Operation Voltage	220-240V,50/60Hz
max. Wattage (1)	2X5W
Dimmable	No
max. Wattage (2)	1X18W

## Illuminant 1

Illuminant Type (1)	E27
Illuminant incl. (1)	Exclusive
Socket Type (1)	E27

## Illuminant 1

Socket Type (1)	GU10
Illuminant Type (1)	GU10-LED
Illuminant incl. (1)	Inclusive
Energy efficiency class (EEI)	F
Info changeability□light source/driver	LED exchangeable by customers, no driver included

## Illuminant 1

Socket Type (1)	LED
Illuminant Type (1)	LED
Illuminant incl. (1)	Inclusive
Lumen Complete	1100
Kelvin Complete	3000K
Light colour Complete	WARM WHITE
Energy efficiency class (EEI)	F
Dimmable	No
Info changeability□light source/driver	LED + driver cannot be exchanged
Nominal Lifetime (in h)	25000
Switching Cycles	15000
Rated Lamp Power (0,1W precision)	24,5
Colour Tolerance (LED, SDCM)	<6
lumen z osłoną	110

## Illuminant 2

Socket Type (2)	LED
Illuminant Type (2)	LED
Illuminant incl. (2)	Inclusive
Lumen Complete	920;400
Kelvin Complete	3000K
Light colour Complete	WARM WHITE;WARM WHITE
Dimmable	No
Info changeability□light source/driver	LED + driver can be exchanged by a specialist

## Illuminant 2

Illuminant Type (2)	E14-ILLU
Illuminant incl. (2)	Exclusive
Socket Type (2)	E14

