


13"x40"x5/16" Ceramic Rectified Flat Field Tile - Matte



White - WHI
100008087



Sand - SAN
100008085



Silver - SIL
100008086



Beige - BEI
100008084

13"x40"x3/8" Ceramic Rectified Wave Deco Field Tile - Matte



White - WHI
100008091



Sand - SAN
100008090



Silver - SIL
100008089



Beige - BEI
100008088



Photo Features 13"x40"x3/8" Rectified
Wave Deco Field Tile - Matte in White.



Donna

Glazed Ceramic


Photo Features 13"x40"x3/8" Rectified Wave Deco Field Tile - Matte in White.

SIZING & PACKAGING

Type	Shape	Beige Item Code	Sand Item Code	Silver Item Code	White Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		100008084	100008085	100008086	100008087	13"x40"x5/16"	Rectified Flat Field Tile - Matte	6	21.53
Deco		100008088	100008090	100008089	100008091	13"x40"x3/8"	Rectified Wave Deco Field Tile - Matte	5	17.98


ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	N/A	N/A	N/A	N/A	Pass (S ≥ 600N/ISO)	> 1.0(Ceramic)	Pass (10545-14=GAISO)




APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential		●			●	
Commercial		●			●	



LEGEND

- Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- Applications & ANSI Technical Specifications do not apply
- * Special Order only



Wet the back of the tile prior to setting. Apply thinset to both the substrate and the back of the tile using a notched trowel. It is recommended to install pattern tiles without an offset. This textured ceramic tile must be sealed prior to grouting. This tile is only intended for wall applications. Conduct a dry mock layout prior to installation to ensure the direction matches on all tiles.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit [bedrosians.com](https://www.bedrosians.com) for current product information. We reserve the right to make product changes at any time without notice.

