

LABEL 1 – UPHOLSTERY LAW LABEL

70 mm (W)

LABEL 2 – ELECTRICAL INFORMATION LABEL

42 mm (W)

SEWING AREA
KEEP CLEAR
(NO TEXT IN THIS AREA)
-- 10 mm / 3/8" --

STITCHING
POSITION
(Top)

UNDER PENALTY OF LAW
THIS TAG NOT TO BE REMOVED
EXCEPT BY THE CONSUMER

ALL NEW MATERIAL
consisting of
POLYURETHANE FOAM PAD 85%
POLYESTER FIBER BATTING 15%

REG. NO. CA 46335
(CA Reg. No. or State Reg. No.)

Certification is made by the manufacturer that the
materials in this article are described in accordance
with law.

MADE BY:
(Manufacturer Name)
ZHEJIANG WONDA ELECTRIC TECHNOLOGY CO., LTD.
(Address) NO.6 YONGSHENG ROAD, HAIRUN SUBDISTRICT,
SANMEN COUNTY, TAIZHOU CITY, ZHEJIANG PROVINCE

IMPORTED BY:
(Company Name) US Tamex Corp
(Address) City of Industry CA 91744

DATE OF DELIVERY: JUN 2026

MADE IN: CHINA
(Country of Origin)

NOTICE
THIS ARTICLE MEETS THE FLAMMABILITY
REQUIREMENTS OF CALIFORNIA BUREAU OF
HOUSEHOLD GOODS AND SERVICES
TECHNICAL BULLETIN 117-2013.

Care should be exercised near open flame or with
burning cigarettes.

COMPLIES WITH U.S. CPSC REQUIREMENTS
FOR UPHOLSTERED FURNITURE FLAMMABILITY.

THE UPHOLSTERY MATERIALS IN THIS PRODUCT:
☒ CONTAIN ADDED FLAME RETARDANT CHEMICALS
☐ CONTAIN NO ADDED FLAME RETARDANT CHEMICALS
The State of California has updated the flammability standard and
determined that the fire safety requirements for this product can
be met without adding flame retardant chemicals. The State has
identified many flame retardant chemicals as being known to, or
strongly suspected of, adversely impacting human health or
development.

For more information, visit: www.dtsc.ca.gov

FOLD HERE
(Do not sew)

FOLD LINE
(Do not sew)

ELECTRICAL INFORMATION

PRODUCT NAME:	POWER RECLINER
PRODUCT MODEL:	81666
RATED VOLTAGE / CURRENT:	100-240V~ 4A
RATED FREQUENCY:	50/60Hz
RATED POWER:	96W
DUTY CYCLE:	Continuous Use
PROTECTION CLASS:	Class II 
PLACE OF ORIGIN:	CHINA
SERIAL NUMBER / DATE CODE: (OPTIONAL)	2024-06
MANUFACTURING YEAR:	2024

IMPORTED BY:
(Company Name) US Tamex Corp
(Address) City of Industry CA 91744



CONFORMS TO
UL STD. 962
CERTIFIED TO
CSA STD. C22.2 No. 68

80 mm
(H)

210 mm
(H)