



ITEM #: RVY-CP8010-L20

IMPORTANT SAFETY INSTRUCTIONS

- To avoid injury or damage, mount only on a surface that is sturdy.
- To avoid electric shock, make sure the electricity is turned off at the main circuit breaker panel. If you are replacing an existing fixture, turn off the following in order: fixture, wall switch, and main fuse or breaker box.
Note: Some types of fuses must be unscrewed to shut the power off.
- If you are unclear as to how to proceed, please consult a licensed electrician.

UNPACK THE FIXTURE: Check the contents of the box. Box should contain all items on the parts diagram.



For any replacement parts or installation issues, please Contact Us!


Email: help@kira-home.com

Facebook/Instagram: @KiraHomeDecor

Phone: 888.208.2085

INSTALLATION INSTRUCTIONS

1. Secure Mounting Plate (A) to the junction box (not included) using Mounting Screws (B) provided.
2. Adjust Wire (G) to desired hanging length using the side screw on Wire Grip (E). Lock Wire (G) in place with Hex Key (F). Remove any excess Wire (G), leaving approximately 10 inches beyond desired hanging length.
Note: Apply gentle pressure when removing/replacing the screw to avoid stripping.
3. Using the wire graph below, connect the appropriate wires from the fixture to the corresponding wires in the electrical junction box (not included) and secure Wire Connectors (C).



- A.** Connect the ground wire (bare copper or green) from your fixture to the:
 - 1) ground wire in the junction box, or
 - 2) ground screw in the junction box
- B.** Connect the BLACK house wire to fixture hot wire that corresponds to diagram (black, round & smooth, white/grey with tracer, brown/gold without tracer).
- C.** Connect the WHITE house wire to fixture neutral wire that corresponds to diagram (white, ribbed/ridged, white/grey without tracer, brown/gold with tracer).

4. Place Canopy (D) against the ceiling and secure the fixture in place by screwing Wire Grip (E) and the nipple into Mounting Plate (A).
5. Using Color Temperature Switch (J) within Shade (H), choose color temperature best suiting your needs.
6. Gently push Diffuser (I) into the bottom of Shade (H). Diffuser (I) should sit above the lip of Shade (H).

Enjoy your new fixture!

Kira Home

ITEM #: RVY-CP8010-L20 - PARTS DIAGRAM

HELPFUL TOOLS: Safety Goggles, Screwdriver, Ladder, Measuring Tape

