Project:

Fixture Type:

Location:

Contact:

Wall mounted • Damp location listed



Description:

This product features a thin, acrylic lens that provides even illumination. This specially designed 48in. linear bath fixture delivers ambient light to surfaces free of shadows. This product is a perfect addition to modern applications. An integrated LED source provides energy and cost savings benefits. Can be installed vertically or horizontally.

Specifications:

- Brushed Nickel (plated)
- Aluminum Construction
- White Acrylic diffuser
- The white acrylic shade provides even illumination
- Square end caps and back plate are finished in Brushed Nickel
- The LED light is diffused to create an even glow
- Ideal for residential, commercial and multi-family applications
- Mount horizontally or vertically on the wall in bath and vanity settings
- Measures 48in W x 4-3/4in ht.
- 44w integrated LED, 3,300 delivered lumens 75 lumens/watt, 3000K color temperature, 90+ CRI.
- + $\,$ ETL Safety listed for use in damp locations
- Compatible with many ELV dimmers
- These products are designed for exceptional quality, reliability, and functionality
- Includes installation instructions and mounting hardware
- Coordinating fixtures available
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- 6" of wire supplied
- · Complies with "Americans with Disabilities Act" ADA
- ENERGY STAR[®] qualified
- Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	44w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	
Lumens/LPW (Delivered)	3300/75 (LM-79)
ССТ	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
FCC	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30°C
Warranty	5-year limited warranty
Labels	cETLus Damp location listed
	ENERGY STAR [®] qualified
	Meets California Title 24 JA8-2016

Images:



Dimensions:

Width: 48" Depth: 3-1/2" Height: 4-3/4" H/CTR: 2-3/8" (horizontal)

Glass Width: 47-1/8" Height: 3" Wall mounted • Damp location listed



Dimming Notes:

is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron NTELV-300	
Lutron DVELV-300P	
Lutron Caseta	
Leviton 6681	
Lutron AYCL-153P	
Lutron MAELV-600	
Lutron AWRMG-EAW	

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.