

# LP1315R




## Maximum Brightness LED Flashlight

9 AA Batteries



### Features

- Constructed with aircraft-grade aluminum
- Long range LPE optics
- Patented TackGrip molded rubber grip
- Ergonomic side button
- IPX4 waterproof rating
- Batteries included (9 AA)

| ANSI/PLATO FL1 STANDARD |  |  |   |
|-------------------------|--|--|---|
| MODES                   |  LUMENS |  RUN TIME |  BEAM DISTANCE |
| High                    | 1650 lm  | 2h 30m   | 330m  |
| Low                     | 600 lm   | 6h   | 190m  |
| Strobe                  | 1650 lm  | --   | --  |

### Operation Instructions

**On/Off:** Press and release the button on the side of the light to turn the light on and off.



**Cycle Modes:** Turn flashlight on and off quickly and repeatedly to cycle through modes (High/Low).

Light automatically resets to High mode when turned off for longer than 2 seconds.

**Hidden Strobe On/Off:** Press and hold button for 3 seconds to activate hidden strobe. Flashlight will remain in hidden strobe mode until it is deactivated by pushing and holding the button for 3 seconds again.

### Battery Replacement

The LP1315R uses 9 AA batteries. To replace the batteries, turn the tail cap counterclockwise to remove it. Tip the light downward to slide out the battery case which contains the batteries. Remove the batteries from the case and insert new batteries according to the (+/-) symbols found on the case. For best results, we recommend using brand new alkaline batteries that are the same voltage and brand. Re-insert the battery case into the flashlight. Re-attach the tail cap by pressing down lightly and turning it clockwise until tight.



If you know it will be a while between uses, we suggest removing the batteries from the flashlight and storing it in a dry, protected place.

### Product Warranty

The LP1315R has a Limited Lifetime Warranty Against Manufacturer's Defects from time of purchase. For warranty claims please contact us by calling 801-553-8886 or sending an email to [info@simpleproducts.com](mailto:info@simpleproducts.com)