

# HR-3LED-T418

3.5" Tesla™ LED 30°-45° Adjustable Trim

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

## PRODUCT DESCRIPTION

Minimum profile, round 30° to 45° adjustable trim with interior open reflector.

## FEATURES

- 3.5" aperture
- Damp location listed
- 30° visual cutoff angle for glare control
- Adjustable fixtures are ideal for sloped ceiling applications
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

## SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

**Power Consumption:** 21.5W

**Dimming:** 0-10V Dimming: 100%-10%  
ELV Dimming: 100%-15% (120V only)

**Mounting:** Two heavy gauge retention clips hold trim firmly to housing.

**Finish:** Powder coated white  
Electroplated brushed nickel and copper bronze

**Standards:** ETL & cETL Listed.

## TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Finish
<b>HR-3LED-T418</b> 30° to 45° Adjustable	<b>S</b> 15°	<b>27</b> 2700K	85	645	1340	<b>BN</b> Brushed Nickel <b>CB</b> Copper Bronze <b>WT</b> White
		<b>W</b> 3000K	85	685	1578	
		<b>9W</b> 3000K	90	630	1561	
		<b>35</b> 3500K	85	725	1705	
		<b>C</b> 4000K	85	725	1543	
	<b>N</b> 28°	<b>27</b> 2700K	85	690	2099	
		<b>W</b> 3000K	85	745	2341	
		<b>9W</b> 3000K	90	685	2072	
		<b>35</b> 3500K	85	750	2366	
		<b>C</b> 4000K	85	765	2540	
	<b>F</b> 41°	<b>27</b> 2700K	85	660	3617	
		<b>W</b> 3000K	85	760	4034	
		<b>9W</b> 3000K	90	699	2717	
		<b>35</b> 3500K	85	755	4238	
		<b>C</b> 4000K	85	735	4201	

**HR-3LED-T418**  -  -

Example: **HR-3LED-T418F-C-BN**

**COMPATIBLE HOUSINGS** See individual housing spec sheets for complete information.

## REPLACEMENT MODULES

Model	Input	Notes
<b>HR-3LED-H18D1-ICA</b>	120V-277V	Allows adjustment in one direction when used with adjustable trims Ceiling thickness: 1/2" - 3/4"
<b>HR-3LED-H18D1-ICAC</b>		
<b>HR-3LED-H18D-ICA</b>	120V-277V	Allows adjustment in any direction when used with adjustable trims Ceiling thickness: 1/2" - 3/4"
<b>HR-3LED-H18D-ICAC</b>		
<b>HR-3LED-H18D-EMICA</b>		
<b>HR3LED-H18D-EMICAF</b>	277V	Ceiling thickness: 1/2" - 3/4"

Reflectors	
Spot	<b>SL-REF-LUX10-S</b>
Narrow Flood	<b>SL-REF-LUX10-N</b>
Flood	<b>SL-REF-LUX10-F</b>

LED		
2700K	85 CRI	<b>LXS8-PW27</b>
3000K	85 CRI	<b>LXS8-PW30</b>
3000K	90 CRI	<b>LXS9-PW30</b>
3500K	85 CRI	<b>LXS8-PW35</b>
4000K	85 CRI	<b>LXS8-PW40</b>

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760