The five-blade fan beautifully accessorizes any room. A simple, modest look combined with superior air flow, this fan was built for comfort. We versatility makes it ideal for any room in the house.

FEATURES	SPECS	CEILING DROP DIMENSIONS
Heavy-Duty, 3 Speed Reversible Motor	Blade Sweep 52"	 +- D -+
Dual Mount	Number of Blades 5	
6" Downrod (Included)	Blade Pitch 13°	
Limited Warranty	Motor Size (MM) 172 x 17	<mark>+-</mark> C
Custom Blades (Included) Integrated	AMPS (HI Speed) <1	B A
LED Light Source (Dimmable) ICS	Watts (HI Speed)	, Ē ,
Remote & Wall Controls Included	Shipping Wt. (lbs.)	
	CU. FT. in Carton 1.65	
LED Specs: Color Temp 3000K Lumens 1,650 lm CRI 90 Watts 19 LED Module is Guaranteed for 3 Years	Airflow* (Cubic Feet Per Minute)	A: 6" DR - 15.07" B: 6" DR - 10.86" C: 11.17" E: 8.78"
	Electricity Use* Watts	D: 5.91" DR = Downrod
	Airflow Efficiency* (CFM Per Watt)	

UNIPACK

"Compare: 49" to 60" ceiling fans have airflow efficiencies ranging from approximately 51 to 176 cubic feet per minute per watt at high speed."



FAN CONTROL OPTIONS

ICS Remote and Wall Controls (Included)

