# **DOUBLE SPOT**

# **Endurance Wallpack**



| D | $D \cap$ | וחי | ICT      | DEC | CRIP | $ci \cap Ni$ |
|---|----------|-----|----------|-----|------|--------------|
| г | nυ       | יטי | <b>J</b> | DES | CNIF |              |

Die cast aluminum factory sealed housings with patent pending design for a water and dust proof IP66 rated outdoor luminaire

#### **FEATURES**

- IP66 and ETL & cETL Wet Location Listed
- Factory-Sealed LED Light Engine
- Energy Star® rated
- Die-Cast Aluminum Construction
- 120V Direct Wire No Driver Needed
- Photo/Motion Sensor Sold Separately
- Smooth and Continuous ELV Dimming

| Fixture Type:   |  |
|-----------------|--|
| Catalog Number: |  |
| Project:        |  |
| Location:       |  |

## **SPECIFICATIONS**

**Construction:** Die-cast aluminum **Power:** Line Voltage input (120V)

**CRI:** 85

Dimming: 100% - 10% with Electronic Low Voltage (ELV) dimmer

Finish: Architectural Bronze, and White

**Standards:** Energy Star®, IP66, Wet Location, ETL & cETL Listed **Operating Temperature:** -40°C (-40°F) to 40°C (104°F)

Rated Life: 43,000 hours

#### **ORDER NUMBER**

| Power       | Comparable   | Color Temp     | Delivered<br>Lumens | Finish                                   |
|-------------|--------------|----------------|---------------------|--|
| 30W         | 150W Halogen | 3000K<br>5000K | 965 x2<br>1030 x 2  | Architectural Bronze Architectural White |
| <br><b></b> |              |                |                     |  |

### **ACCESSORIES**





Photocell Sensor (120V) Black Gray White