

ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

1. Push the plastic nut in the holes pre-drilled in the wall in place.
2. Let the two supplied screws(B) pass through the holes specially provided on the mounting plate and lock them.
3. Fix the mounting plate to the outlet box using 2 outlet box screws. Thread two screws(A) into plastic nuts.
4. Make wire connections:
 - Attach ground wire to house ground wire using a wire nut or attach them to the mounting plate with a green ground screw.
 - Attach white wire from light to white wire from power source with a wire nut.
 - Attach black wire from light to black wire from power source with a wire nut.

Observing: positive wire with positive wire, negative wire with negative wire, ground wire with ground wire.
5. Tuck the wire connections neatly into the outlet box.
6. Aim the faceplate to the two supplied screws(B), then fasten it with the two ball nuts.
7. Place the glass shade onto the socket and secure it with the socket ring.
8. Install bulbs.(not included) (Please do not exceed the maximum capacity which is recommended on the fixture.)
9. Turn on the power at fuse or circuit box.

