


## Hardware Package(included):



Mounting Bracket(A)



Mounting Screw(B)



ScREW Nut(D)



Wire Nut(E)



Nut(F)



Nut Gasket(H)

# ASSEMBLY AND INSTALLATION INSTRUCTIONS

**WARNING:** TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

NOTES: 1. Before installing, consult local electrical codes for wiring and grounding requirements.  
2. READ AND SAVE THESE INSTRUCTIONS.

## Installation Steps

Turn off the power at fuse or circuit box

Assembly of the fixture body

Check if all the accessories are included.

Step: 1. Attach the Mounting Bracket to the outlet box by using two mounting screws.

Step: 2. Pull out the source wires from the outlet box. Make wire connections using wire nuts as follows:

---Connect the hot wire (usually black insulation) from the fixture to the black wire from the power source.

---Connect the neutral wire (usually white insulation) from the fixture to the white wire from the power source.

---Attach the fixture grounding wire (usually bare wire) connect it to the house grounding wire with the wire nut.

--- Carefully put the wires back into the outlet box.

Step: 3. Attach the fixture body to the Mounting Bracket by inserting Fixture Screws into holes on back plate, and then secure it with two ball nuts.

Step: 4. Install E12 bulb (not included). Check relamping label at socket area or packaging for maximum allowed wattage.

Step: 5. The glass lampshade is fitted onto the lamp holder.

## Attention

1. Please install it by a licensed electrician.

2. Due to the different display, the actual color can be different from the image.

3. Due to the manual measurement of lamp body size, there may be a deviation of 1/2 inch.

4. If there are any quality problems, missing parts or other something wrong with the item, please feel free to contact us and we will try our best to help you.

