

# illuminator

## "LustraL OD-50 "model

### 1. Generalprovision

The chandelier is strong and light in construction.

The housing is made of metal and plastic for high safety performance.

The chandelier is strong and light in construction.

The housing is made of metal and plastic for high safety performance.

The diameter of this lamp is about 50 cm. Steel wire is available, with a maximum length of 150 cm. The package size is 26 x 27 x 1 cm. Connect the 220 volt pod. You need a G9 shell  
It takes eight floors and eight lights.

The total power of the luminaire must not exceed 25 watts. The lamp is Reliable light source of 14-25 m2. Nymplomat 21 . lpr

### 2. He was on heroin.

1. Rundlicher chandelier - 1

2.glassware.

3. Landing gear :1.

4.Screw mounting. - 2.

5. Firmware - 1.

6. Traffic light pass.

### 3. Chandelier recording.

1.Fix the bottom plate to the ceiling and check the reliability of the ion device.

2. Make connections.

(Note :\* Power must be cut off when building the chandelier.)

3. Keep cables and wires ready (height can be adjusted after installation  
Think of the cables and cables on the base.

4. Bolt the base of the chandelier.

5. Fold with the glass twigs to form a rod.

"Be careful not to insert decorative branches into the handprint."

6. Complete led lights.

7. Easily transfer the hamster to a decorative branch and disperse it.

8. Finally, the exit height was adjusted.

To increase the size of the wire, you have to push the sled to the floor and keep it at the correct length.

To secure the cable, we should put the case back in the case.

Open the starting position and tie the rope.

Push down on the rope to shorten the length.

