



PRODUCT DESCRIPTION

Multiple mid-powered LEDs illuminate the acrylic diffuser uniformly without socket shadows which are common in conventional flush mounts.

FEATURES

- Energy Star® rated
- Wet Location Listed
- CEC Title 24 Compliant
- CSA listed
- ADA compliant
- Wall or Ceiling Mount
- Opaque acrylic diffuser
- Multiple LED array for uniform illumination
- 120VAC - no driver needed
- Smooth and continuous ELV dimming
- 36,000 hour rated life
- 5 year warranty

SPECIFICATIONS

- Construction:** Steel with white acrylic diffuser
- Input:** 120VAC
- ELV Dimming:** 100% - 10% Electronic Low Voltage
- Harmonic Distortion (THD):** 16% for Input Current at 120VAC
- Operating Temperature:** -35°C (-31°F) to 50°C (122°F)

ORDERING NUMBER

		Watt	Mounting	Color Temp	CRI	LED Lumens	Delivered Lumens	Finish
	FM-304	12W	Retrofit over a 4" recessed can or install over a junction box	930	3000K	90	670	BN Brushed nickel
								BZ Bronze
								WT White
	FM-306	15W	Retrofit over a 5" or 6" recessed can or install over a junction box	930	3000K	90	1110	BN Brushed nickel
				940	4000K	90	1165	BZ Bronze
	FM-306	15W	Install over a junction box only	930JB	3000K	90	1110	WT White

FM-30 - -