

foam type: 23050GN date: 04.22.16
typical physical properties

	<u>average</u>	
color	lt green	may vary slight
density	2.30	pounds per cubic foot
indentation force deflection:		
25% deflection	47--53	lbs per 50 square inches, sample size 15" x 15" x 4"

porosity (air flow)	2.9	cubic feet per minute
rebound	n/a	%
tensile strength	n/a	pounds per square inch
tear resistance	n/a	pounds per inch
ultimate elongation	n/a	%

compression set:		
90% deflection	n/a	% height loss

dynamic flex test - 24 hr		
height loss	n/a	% height loss
25% IFD loss	n/a	% IFD loss

flammability test# CAL117-2013

*unless otherwise stated, tested according to ASTM-D3574

flammability tests are performed under controlled laboratory conditions. Results in no way indicates foam performance in an actual fire. Polyurethane foam should be stored and handled with care. It should be kept away from sources of heat and flame at all times.

This information is furnished without warranty, representation, inducement or license of any kind, including but not limited to the implied warranties of merchantability and fitness for a particular use or purpose, except that it is accurate to the best of Elite's knowledge or obtained from sources believe by Elite to be accurate. Elite does not assume any legal responsibility for use or reliance upon same. Customers are encouraged to conduct their own tests.