

DURHAM MFG®

Est. 1922



FM Approved Flammable Safety Cabinet with Legs

- Sturdy all welded 16 gauge double wall steel construction
- Choice of manual or self closing doors
- 2" wide louvers support shelves, adjustable on 4" centers
- 2" Deep leak proof base
- Safely contains hazardous chemicals reducing the risk of fire
- Electrical ground on bottom right hand side to aid in the elimination of an electrostatic discharge
- Units come fully assembled and ready for use
- Improved security with recessed lockable paddle latch and 3 point locking system
- 6" Box style legs allows for lagging to the floor, moving with forklift, and cleaning under the cabinet
- Bunged air vents on each side of the cabinet allows for ventilation
- Safety yellow powder coat finish

Model	Gallon Capacity (L)	Dimensions: In (mm) - WxDxH	Shelves	Optional Shelf Part #	Door Style	Ship Wt.
1012ML-50	12 (45)	23" x 18" x 41" (584 x 457 x 1041)	1	FS-SH-1419	Manual	178 lbs.
1012SL-50	12 (45)	23" x 18" x 42-3/8" (584 x 457 x 1076)	1	FS-SH-1419	Self Closing	186 lbs.
1030ML-50	30 (114)	43" x 18" x 50" (1092 x 457 x 1270)	1	FS-SH-1439	Manual	304 lbs.
1030SL-50	30 (114)	43" x 18" x 51-3/8" (1092 x 457 x 1302)	1	FS-SH-1439	Self Closing	328 lbs.
1045ML-50	45 (170)	43" x 18" x 71" (1092 x 457 x 1803)	2	FS-SH-1439	Manual	428 lbs.
1045SL-50	45 (170)	43" x 18" x 72-3/8" (1092 x 457 x 1838)	2	FS-SH-1439	Self Closing	442 lbs.
1060ML-50	60 (227)	34" x 34" x 71" (834 x 864 x 1803)	2	FS-SH-2930	Manual	542 lbs.
1060SL-50	60 (227)	34" x 34" x 72-3/8" (834 x 864 x 1838)	2	FS-SH-2930	Self Closing	566 lbs.
1090ML-50	90 (340)	43" x 34" x 71" (1092 x 864 x 1803)	2	FS-SH-2939	Manual	620 lbs.
1090SL-50	90 (340)	43" x 34" x 72-3/8" (1092 x 864 x 1838)	2	FS-SH-2939	Self Closing	656 lbs.

FOB TX

Phone: 860.349.3427 - Fax: 860.349.8235
www.durhammfg.com - info@durhammfg.com

DURHAM MFG[®]

Est. 1922



FM Approved Flammable Safety Cabinet

- Sturdy all welded 16 gauge double wall steel construction
- Choice of manual or self closing doors
- 2" wide louvers support shelves, adjustable on 4" centers
- 2" Deep leak proof base
- Safely contains hazardous chemicals reducing the risk of fire
- Units come fully assembled and ready for use
- Electrical ground on bottom right hand side to aid in the elimination of an electrostatic discharge
- Improved security with recessed lockable paddle latch and 3 point locking system
- Bunged air vents on each side of the cabinet allows for ventilation
- Safety yellow powder coat finish

Model	Gallon Capacity (L)	Dimensions: In (mm) - WxDxH	Shelves	Optional Shelf Part #	Door Style	Ship Wt.
1004M-50	4 (15)	17-3/8 x 18-1/8 x 22-1/8 (442 x 461 x 562)	1	FS-SH-1413	Manual	104 lbs.
1004S-50	4 (15)	17-3/8 x 18-1/8 x 23-3/8 (442 x 461 x 593)	1	FS-SH-1413	Self Closing	110 lbs.
1012M-50	12 (45)	23" x 18" x 35" (584 x 457 x 889)	1	FS-SH-1419	Manual	159 lbs.
1012S-50	12 (45)	23" x 18" x 36-3/8" (584 x 457 x 924)	1	FS-SH-1419	Self Closing	167 lbs.
1012MH-50	12 (45)	43 1/8" x 18 1/8" x 18 1/8" (1095 x 461 x 461)	1	FS-SH-1439	Manual	165 lbs.
1022M-50	22 (83)	23-5/16 x 18-1/8 x 65 (592 x 461 x 1651)	2	FS-SH-1419	Manual	283 lbs.
1022S-50	22 (83)	23-5/16 x 18-1/8 x 66-3/8 (592 x 461 x 1686)	2	FS-SH-1419	Self Closing	296 lbs.
1030M-50	30 (114)	43" x 18" x 44" (1092 x 457 x 1118)	1	FS-SH-1439	Manual	285 lbs.
1030S-50	30 (114)	43" x 18" x 45-3/8" (1092 x 457 x 1153)	1	FS-SH-1439	Self Closing	309 lbs.
1045M-50	45 (170)	43" x 18" x 65" (1092 x 457 x 1651)	2	FS-SH-1439	Manual	409 lbs.
1045S-50	45 (170)	43" x 18" x 66-3/8" (1092 x 457 x 1686)	2	FS-SH-1439	Self Closing	423 lbs.
1060M-50	60 (227)	34" x 34" x 65" (834 x 864 x 1651)	2	FS-SH-2930	Manual	509 lbs.
1060S-50	60 (227)	34" x 34" x 66-3/8" (834 x 864 x 1686)	2	FS-SH-2930	Self Closing	533 lbs.
1090M-50	90 (340)	43" x 34" x 65" (1092 x 864 x 1651)	2	FS-SH-2939	Manual	587 lbs.
1090S-50	90 (340)	43" x 34" x 66-3/8" (1092 x 864 x 1686)	2	FS-SH-2939	Self Closing	623 lbs.

FOB TX

Phone: 860.349.3427 - Fax: 860.349.8235
www.durhammfg.com - info@durhammfg.com