

Field Tile Sizes



Sale - SAL
ASCSTOSAL1224
12"x24" Rectified Field Tile - Matte



Sabbia - SAB
ASCSTOSAB1224
12"x24" Rectified Field Tile - Matte



Cenere - CEN
ASCSTOCEN1224
12"x24" Rectified Field Tile - Matte



Terra - TER
ASCSTOTER1224
12"x24" Rectified Field Tile - Matte



Sale - SAL
ASCSTOSAL3636
36"x36" Rectified Field Tile - Matte



Sabbia - SAB
ASCSTOSAB3636
36"x36" Rectified Field Tile - Matte



Cenere - CEN
ASCSTOCEN3636
36"x36" Rectified Field Tile - Matte



Terra - TER
ASCSTOTER3636
36"x36" Rectified Field Tile - Matte

2"x2" Mosaic - Matte (12"x12" Sheet)



Sale - SAL
ASCSTOSAL22MO



Sabbia - SAB
ASCSTOSAB22MO



Cenere - CEN
ASCSTOCEN22MO



Terra - TER
ASCSTOTER22MO

Stone Valley

Glazed Color Body Porcelain

Photo Features 12"x24" Rectified Field Tile - Matte in Cenere.


SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		ASCSTO***1224	12"x24"	Rectified Field Tile - Matte	6	11.63
		ASCSTO***3636	36"x36"	Rectified Field Tile - Matte	2	17.44
Trim		ASCSTO***324BN	3"x24"	Bullnose - Matte	10	-
Mosaic		Ø ASCSTO***22MO	12"x12" Sheet	2"x2" Mosaic - Matte	5	-

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	4	Unaffected	9	Pass (1,300 ISO)	≤ 0.5%	Unaffected


Shade Variation



V3-Moderate

APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	◻	◻	•	◻	◻
Commercial	•	◻	◻	•	◻	◻



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- Ø Applications & ANSI Technical Specifications do not apply
- * Special Order only



Use of a leveling system during installation is strongly recommended

This tile must be installed with a premium modified thinset. Do not use mastic.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

MKTTERASCSTO
REV. 1/2020

bedrosians.com

