Project:		
ixture Type:		
_ocation:		
Contact:		

One-Light LED Flush Mount

Ceiling flush mounted · Damp location listed





Description:

One-light LED Flush Mount with a white glass diffuser and replaceable LED Module in an Antique Bronze finish.

Specifications:

- · Antique Bronze (painted)
- · Steel Construction
- · Opal glass bowl
- · Replaceable LED module.
- · 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Ceiling pan covers a standard 4" octagonal recessed outlet box
- · Mounting strap for outlet box included
- 6" of wire supplied
- · ENERGY STAR® qualified

Performance:

Number of Modules	1	
Input Power	17w	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW (Source)	1211/71.2 (LM-82)	
Lumens/LPW (Delivered)	954/59.3 (LM-79)	
ССТ	3000 K	
CRI	90 CRI	
Life (hours)	60,000 (L70/TM-21)	
FCC	Meets FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30 °C	
Warranty	5 year warranty	
Labels	cCSAus Damp location listed	
	ENERGY STAR® qualified	

Images:



Dimensions:

Diameter: 7-1/2" Height: 4-7/8"

One-Light LED Flush Mount

Ceiling flush mounted • Damp location listed



Dimming Notes:

This fixture is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.