



John Boos & Co.
315 S. First Street
Effingham Il 62401
(217) 347-7701
Fax (217) 347-7705

ASSEMBLY INSTRUCTIONS BRISTOL FARM AND SARATOGA BLOCK

PARTS: (1) Block top
(4) Block legs

HARDWARE: (4) 3/8"x2 1/2" lag bolts
(4) washers
(4) Adjustable floor glides w/t-nuts or
4 casters-(optional)

TOOLS REQUIRED: (1) 9/16" wrench
(1) Hammer

CAUTION: Make certain assistance is available when setting block upright to avoid injury to yourself or the block.

SUGGESTION: Applying bar soap to the bolt or screw threads will make them much easier to insert and lessen the chance of breakage.

INSTRUCTIONS: (1) Remove all contents of box, making sure assembly area is flat and clean.
(2) Place top face down on a rug, carton, or other protected surface.
(3) Attach each of four legs to the metal brackets at each corner, using one 3/8" x 2 1/2" lag bolt with washer. Tighten securely. Do not overtighten!
(4) Tap T-nuts into the bottom of the leg in predrilled hole. Screw in adjustable floor glides or tap the caster sleeves into predrilled holes and insert casters.
(5) Turn block right side up. Your block is now ready to use. ENJOY!

Be sure to follow the maintenance and care guidelines on the enclosed care sheet for your new John Boos product.

NOTE: When moving block, never pick up one end and drag the other. This will cause the legs to become loose. To move, lift block from both ends and carry, making sure assistance is available.

