

After approximately 15,000 uses, there will be a small amount of blue Odor Barrier Liquid on top of the Drain Insert. This indicates it is time to change out the Odor Barrier Liquid and the Drain Insert.



1. Using the key provided, screw the key into the key hole of the drain insert and fill with water.



2. Pull upward on insert to remove.



3. Rinse the open trap with water.



4. Replace the new insert, press down until you feel and hear a slight popping sound.



5. Fill with 32 ounces of water.



6. Pour into 1-10 ounce bottle of odor barrier liquid.

**In Mexico:**  
Customer Service Manager  
AS Maquila, S.A. de C.V.  
Via Morelos #330  
Col. Santa Clara  
Ecatepec 55540 Eco. Mexico  
[www.americanstandard.com.mx](http://www.americanstandard.com.mx)

**In Canada:**  
AS Canada ULC  
2480 Stanfield Rd.  
Mississauga, Ontario  
Canada L4Y 1S2  
Toll Free: (800) 387-0369  
[www.americanstandard.ca](http://www.americanstandard.ca)

**In the United States:**  
American Standard Brands  
P.O. Box 6820  
Piscataway, New Jersey 08855  
Attention: Director of Consumer Affairs  
For residents of the United States, warranty information may also be obtained by calling the following toll free number: (800) 442-1902  
[www.americanstandard-us.com](http://www.americanstandard-us.com)