



E26 LED only
 2*E26 Max 25W
 Not included

Haven Flush Mount Instruction

Safety Warning

Please turn off power at breaker panel before installation.

Installation Steps

- **Step 1: Attach the Mounting Plate**

Fasten the rectangular hanging plate to the ceiling-mounted junction box with the two #8-32 screws provided. The threaded center rod should point downward and sit level.

- **Step 2: Wire the Fixture**

1. Hot: Connect fixture black to house black (hot).
2. Neutral: Connect fixture white to house white (neutral).
3. Ground: Connect fixture green/bare to house ground/bare copper or to the green screw on the plate. Twist wire connectors clockwise and tuck the splices neatly inside the box.

- **Step 3: Mount the Fixture Body**

Raise the lamp body up to the hanging plate and thread the center stem into the plate. Rotate clockwise until the body is snug against the ceiling.

- **Step 4: Install the Ceiling Cover**

Slide the rectangular ceiling plate upward along the stem until it meets the ceiling surface.

- **Step 5: Lock the Ceiling Plate**

Thread the decorative retaining ring upward onto the stem to clamp the ceiling plate firmly in place. Hand-tighten only.

- **Step 6: Add the Outer Shade**

Carefully lift the fabric-wrapped lampshade over the stem and position it so the upper rim seats flush against the retaining ring.

- **Step 7: Insert the Diffuser**

Place the cloth diffuser plate inside the metal support ring.

- **Step 8: Secure the Bottom Ring**

Push the metal ring upward into the bottom of the shade until it rests against the diffuser.

- **Step 9: Tighten Side Screws**

Evenly tighten the three small screws on the ring to lock the diffuser and shade in place.

Final Check

Once installation is complete, restore power at the breaker panel and test the light fixture.

Please contact us if you have any problems installing the lampshade. We will work you through the process.