



Pre-assembly



1. Two or more people are required for assembly.




2. You will need one or more stepladders.



3. Wearing protective gloves is recommended.



4. You may need a safety hat.



5. Please use a Phillips screw driver.



6. For ease of construction, you may need a drill.



7. You may need a safety goggle.


















8. Do not fully tighten screws prior to complete assembly.

Warning & Attention

-Try to assemble this product on the flat ground, otherwise it is difficult to carry out;


-It would be much easier to assemble the product with three or more people;

-After assembly, please check whether all screws are tightened, to prevent parts from falling apart.

2	L=90x90x1760mm  A 4x	L=90x90x720mm  A1 2x	L=90x90x720mm  A2 2x
	L=70x27x1478mm  C 1x	L=70x27x1490mm  C1 1x	
	L=70x27x1478mm  C2 1x	L=70x27x1490mm  C3 1x	
	L=100x25x1250mm  D 1x	L=100x25x1565mm  D1 1x	
	L=100x25x1565mm  D2 1x	L=100x25x1250mm  E 1x	
	L=100x25x1565mm  E1 1x	L=100x25x1565mm  E2 1x	
	L=70x25x1478mm  F 2x	L=70x25x1490mm  F1 2x	
	L=70x27x1478mm  G 1x	L=70x27x1490mm  G1 1x	


Part list

L=Ø19x1720mm




(H) 5x

L=Ø19x1720mm




(H1) 5x

L=Ø16x1747mm




(J) 1x

L=Ø16x1747mm




(J1) 1x

L=Ø16x1747mm




(K) 1x

L=Ø16x1747mm



(K1) 1x

L=20x10x1747mm



(L) 1x

L=20x10x1747mm



(L1) 1x



(B) 2x




(B1) 2x



(M) 1x




(M1) 1x



(N) 5x



(P) 8x



(Q) 1x



(R) 1x



(S) 1x



(S1) 4x



(S2) 10x



M6x16

(1) 85x



M6x15

(2) 32x




M6x20

(3) 3x




M6x28

(4) 3x




M6x85

(5) 6x






- A 4x
- A1 2x
- A2 2x
- B 2x
- B1 2x
- Q 1x
- 1 32x M6x16
- 4

Step1: Connect part A1 and part A, part A2 and part A on the side of the wall using screws 1# and part B1 as shown in diagram.




Then connect part A2 and part A, A1 and part A on the other side using screws 1# and part B.

Step 2: As shown in the figure, use screws 1# to connect part C and C1, and also connect part C2 and C3 together. At the same time, connect five sliders (part S2) on each side.




C 1x



C1 1x



C2 1x



C3 1x



S4

Q 1x




S2 10x






M6x16

1 8x



D 1x




D1 1x

D2 1x

E 1x

E1 1x

E2 1x
 S4
Q 1x

1 16x M6x16
6

Step 3: Link part D and part D1, part D and part D2 using screws 1# as shown in diagram1# as shown in diagram. And link part E and part E1, part E and part E2 using screws 1# as shown in diagram.




F 2x

F1 2x

G 1x

G1 1x

R 1x

S4


Q 1x

S 1x

S1 4x

1 12x
7

Step 4: Link part F and F1, part G and G1 using screws 1# as shown in diagram. And connect the sliders(part S1 and part S). Then hang part R on the outside slider of part G1.





M6x15


2 16x

S6



Q 1x

Step 5:



Connect part D2 with A1, D1 with A2 using screws 2# as shown in diagram. Also, connect part E1 with A2, E2 with A1 using screws 2# as shown in diagram.



M6x15


2 16x

S6




Q 1x

Step 6:



Connect part C2 with A1, C3 with A2 using screws 2# as shown in diagram. Also, connect part C with A2, C1 with A1 using screws 2# as shown in diagram.



M6x85

5 3x




S4


Q 1x

Step 7:

As shown in the figure, use screws 5# to connect part F with beams (part D1&D2), and also connect part F1 with beams (part E1&E2). Then connect part G and G1 with beams (part D&E) in the same way.



H 5x



H1 5x



J 1x





J1 1x




M 1x

Step 8: Insert part J&J1 into the pocket of top roof (part M) as shown in diagram, then insert part H&H1 into the pocket of top roof in turn.







(K) 1x




(K1) 1x




(L)



(L1)




(M1) 1x



(N) 5x

Step 9: Insert part L&K, L1&K1 into the part M1 using part N.






M6x16

2 7x



M6x20

3 3x



M6x85


5 3x



S4

Q 1x

Step 10: Secure the part M1 to the top.





2 10x M6x16




4 3x M6x28




S4

Q 1x

Step 11 : Connect part J and part D1 and connect part H and part H1.



Step 12 :



When the canopy is folded, hang the other end of string (part R) into the hole on the inside of beam (part E) to secure the top roof.


1

(P) 8x



Step 13:

Insert stakes (part P) through the hole of stand plate (part B) into the ground, to stabilize the tent.



13

