

Gooseneck Battery Sensor Faucet w/ Manual Override

MODELS:

- SF-9107: Gooseneck Battery Sensor Faucet
- SF-9107-TMV: Gooseneck Battery Sensor Faucet w/ Thermostatic Mixing Valve

FEATURES:

- Brass construction with polished chrome finish
- Sensor eye at base of faucet
- Powered by six (6) AA batteries included
- Gooseneck spout
- Manual override
- 60 second flow time out feature
- 9/16"-24 UNF supply connection
- Vandal-resistant 0.5 GPM (1.89 L/min) flow control

OPTION:

- TMV: Thermostatic Mixing Valve (A-TMV)

ADD-ONS:

- A-SF-GBLFE: alternate flow aerator group (1.5 GPM, 1.5 GPM laminar and 1.2 GPM)

STANDARDS:

- ASME A112.18.1/CSA B125.1 certified
- NSF/ANSI 61 certified
- NSF/ANSI 372 certified
- ADA compliant

WARRANTY:

Visit www.speakman.com for full product warranty information

- Limited Lifetime Warranty (residential)
- 5 Year Limited Warranty (commercial)




Information continues on next page

All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice.

Architect/Engineer Approval Space:

P: 800-537-2107
 F: 800-977-2747
 W: WWW.SPEAKMAN.COM
 R: 02-NOVEMBER 2019

Gooseneck Battery Sensor Faucet w/ Manual Override



All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice.

Architect/Engineer Approval Space:

P: 800-537-2107
 F: 800-977-2747
 W: WWW.SPEAKMAN.COM
 R: 02-NOVEMBER 2019