

location:

METALWORKS OUTDOOR

WE TALWOTTS OUT

SPECIFICATIONS:

DESCRIPTION

Wall-mounted heavy-guage aluminum sconce. Four sizes available. **ADA-compliant.**

LAMPING

Standard: 60W A19 120V incandescent, not included. Optional fluorescent configurations available (see ordering). **LED:** 7W LED Replaceable source 120V, non-dimmable, included.

DIFFUSER

White impact-resistant Acrylic diffuser available in all sizes.

CONSTRUCTION

.080" aluminum housing and faceplate, with a clear or bronze powder coating. Faceplate is secured by stainless steel screws.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 75°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Wet Locations. May be used in Interior or Exterior applications.

METALWORKS LUMINAIRES ARE ASSEMBLED WITH SHEET METAL FABRICATED AND POWDER COATED IN THE USA.









For ordering information, see next page


All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.


METALWORKS OUTDOOR

ORDERING:









FIXTURE	- DIFFUSER -	LAMP OPTIONS -	METAL FINISH
Sconce	Glitter Satin White Glass White Acrylic	1x 60W B10 Incan 1x 18W Quad 120V 1x 7W LED 120V, non-dimmable	Brushed Alum Bronze
FIXTURE	- DIFFUSER	- LAMP OPTIONS	- METAL FINISH
Sconce	Glitter Satin White Glass White Acrylic	2x 60W B10 Incan 1x 26W Quad 120V 2x 7W LED 120V, non-dimmable	Brushed Alum Bronze

FIXTURE	- DIFFUSER -	LAMP OPTIONS -	METAL FINISH
Sconce	White Acrylic	3x 60W B10 Incan	Brushed Alum
		1x 24W T5 120/277V	Bronze
		2x 24W T5 120/277V	
		3x 7W LED 120V,	
		non-dimmable	

FIXTURE	- DIFFUSER -	LAMP OPTIONS -	METAL FINISH
Sconce	White Acrylic	3x 60W B10 Incan	Brushed Alum
		1x 39W T5 120/277V	Bronze
		2x 39W T5 120/277V	
		3x 7W LED 120V,	
		non-dimmable	

Project Information:		

LED SCONCES:

- Total power of only 7 watts
- Non-dimmable
- Rated life: 30,000 hours
- 500 lumens
- CCT: 3000° Kelvin
- CRI: 80+