

# **SPECIFICATIONS FOR KIDSTUFF PLAYSYSTEMS COMPONENTS**

## **Model 7482**

### **Ages 2-5 Playsystem, 3 1/2" OD Posts, Plastic Decks**

**POWDER-COATING:** Powder-coating is a scratch and chip resistant, extremely UV-stable outdoor polyester finish that retains its bright, colorful appearance for years. All steel tubing in the Kidstuff series is powder-coated over galvanizing for additional rust protection. Welds are treated with a zinc-rich powder, oven treated before the color coat. Powder-coating is oven-baked until cured. Powder thickness depends on color, but minimum thickness is 2.8 - 3.0 mils. Every metal part in any Kidstuff playstructure is powder or "plastisol" coated (excluding swing chain and galvanized bridge support elements).

**CLAMP:** The Kidstuff clamp is die cast from aluminum alloy in the USA and then powder-coated. The clamp incorporates a molded-in socket to encompass each pipe end. Clamp halves attach with 5/16" x 1-1/4" socket-head bolts and nylon lock nuts. Pipe end is held in the clamp socket by a 3/8" x 1/2" setscrew. Stainless expansion pins (1/4" x 3/4" to 2") driven through the socket and into the pipe provide additional retention security for components where pull-out could compromise safety or structural integrity. Hardware is stainless steel and is tamper-resistant. Every clamp is also secured to each post with pins (above) at job conclusion to prevent slippage or rotation

**FASTENERS:** Tamper resistant hardware is used throughout every Kidstuff system. Fasteners meet or exceed requirements of ASTM 1487-11 section 4. 2ff. Stainless steel hardware is used almost exclusively (99.5% of applications).

**STEEL TUBING:** Throughout all Kidstuff structures tubing is high-strength steel, galvanized, with a zinc-coated interior. After component fabrication all welds are prefinished with baked-on, zinc-rich polyester powder prior to final color-coat powder application. Outside diameter (OD) is noted in individual specifications. Typically, 1.16" OD tubing is a min. 17 ga., 1.31" OD and 1.50" is a min. 14 ga., 1.90" OD and 2.38" OD are min. 13 ga. Where heavier tubing is employed it is mentioned in the specifications. All tubing is AMERICAN MADE and meets or exceeds applicable ASTM specifications.

All play equipment that children play on shall be in compliance with the current ASTM F-1487 Standard, and with the current Consumer Product Safety Commission Guidelines, with evidence provided with the bid. The play equipment manufacturer shall be ISO 9001-2008 certified.