



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11715** - 9 watt LED Direct Wire Downlight; Gimbaled; 6 inch; 5000K; 120 volt; Dimmable

- Air Tight
- IC Rated



### ELECTRICAL

Technology:	LED
Watts:	9W
Volts:	120V
Lumens:	720L
CRI:	90
CCT (Kelvins):	5000K
Temperature:	Natural Light
Beam Spread :	90
Hours Rated:	40000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	65W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Replaceable Light Source :	No
Connection:	Direct Wired
Power Factor :	>.9
Warranty:	5 Year Limited - Fixtures

### PACKAGING

Each UPC:	045923117152
Each Quantity:	1
Each Dimensions:	6.93 x 4.25 x 6.93
Case UPC:	10045923117159
Case Quantity:	12
Case Dimensions:	14.57 x 13.39 x 14.76

### INFO

Specification Note:	Aiming Angle: 30dg
Min Compartment Size:	Height: 4.72 in.

### PHYSICAL

Finish:	White
Finish Family:	White
Dimensions:	W:6 11/16" H:3 11/16"
Weight (Lbs.):	0.72
Material:	Aluminum / Polycarbonate (PC)

### INSTALLATION

Ceiling Aperture:	5.70 in. Cutout
Max Drywall Thickness:	1-1/8 in.
Sloped Ceiling Compatible:	Yes

### COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	No
UL/ETL Application:	Ceiling
CA Prop 65:	Lead
NOM Certificate No.:	NTEC21EL007844
NOM Expiration Date:	12/29/2022
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

**ACCESSORIES**

---



**80-947**      6" Goof Ring for Remote Driver Installation

---



**80-951**      Rough-In Mounting Plate; 6" with Junction Box

---

**DIMMER COMPATIBILITY**

---

**Leviton** 66ELV

---

**Satco** 86/103

---

**LeGrand** ADTP703TU

---

**Lutron** CTRP-253P

---

**Cooper** DALo6P-C2

---

**Lutron** DVLV-600P

---

**Lutron** DVRP-253P

---

**Leviton** DW6HD

---

**Leviton** IPE04-1L

---

**Leviton** IPL06

---

**Lutron** MA-PRO

---

**Lutron** NTCL-250

---

**Lutron** NTRP-250

---

**Cooper** SALo6P

---

**Lutron** SLV-600P

---

**Cooper** SUF7

---

**Cooper** TALo6P-C2

---