

Soft Stride® Sound-Reducing Cushion Underlayment

70-185

EFFICIENT

Includes adhesive strip and 3" overlap film for linking multiple rolls

PROTECTION

2 mm foam cushions flooring

QUALITY

Anti-crush technology for excellent performance and long life



CLOSED CELL FOAM

For excellent moisture protection




PRODUCT RATINGS


IIC 69	STC 66	Δ Delta 21
------------------	------------------	----------------------

SPECIFICATIONS (+/- 10%):


ITEM#	70-185
R-VALUE (ASTM C518)	0.343
MVTR (ASTM E96)	0.091 lbs/1000 ft ² /24 hrs
INDENTATION (ASTM F1914)	0.036"
COMPRESSION SET (ASTM D3575) @50%	-49.4%
TENSILE STRENGTH (ASTM D3575)	72.3 lbs/in ²
SMOKE DENSITY (ASTM E662)	PASS
FLAMMABILITY (ASTM D2859) to CPSC FF1-70	PASS
UNIT OF MEASURE	12 rolls per case
COVERAGE	100 ft ² per roll 1200 ft ² per case
WIDTH OF ROLL	43.5"
LENGTH OF ROLL	27.5 ft
THICKNESS	2 mm
WEIGHT PER ROLL	2 lbs
DIAMETER OF ROLL	6.25"




Sound Reduction




Moisture Protection



Cushions Flooring



Radiant Heat



Levels Imperfections

Scan here for
PRODUCT
INFORMATION



Soft Stride® is a dense foam underlayment that provides excellent sound reduction under floating laminate and engineered flooring. The closed cell foam design provides excellent moisture protection and fights against mold and mildew. The 3" overlap film helps seal out moisture and easily attaches to adhesive strip.

For use over concrete and wood subfloors.