

INSTALLATION INSTRUCTIONS

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

1. STAINED GLASS SHADE
2. LIGHT CLUSTER
3. 36" CHAIN
4. CANOPY

Caution:

**Be sure power is off at the main breaker box prior to installation.
Read all instructions in their entirety before beginning installation.**

1. Carefully unpack all components and make certain that everything is accounted for.
2. Unscrew Collar from Canopy Loop to release Crossbar.
3. Affix Crossbar w/ Loop to Junction Box.
4. Unscrew Loop at top of Light Cluster Stem and slide Loop off of Lead Wire.
5. Feed Lead Wire and threaded end of Light Cluster Stem up through hole in center of Shade.
6. Slide Loop onto Lead Wire and screw onto Light Cluster Stem.
7. Attach desired length of Chain to Loop on top of Shade.
8. Weave Lead Wire through every 4th link of Chain.
9. Slide Collar and Canopy over Chain and Wire and allow Canopy to rest on top of Shade.
10. Hang Fixture by attaching loose end of Chain to Crossbar Loop.
11. Feed Lead Wires through Crossbar Loop and, following all Local Codes and Procedures, make Electrical connection from Fixture Lead Wires to Supply Wires.
12. Slide Canopy and Collar up Chain to ceiling and thread Collar onto Loop until secure.
13. Install 8 E12 60Watt Bulbs(not included) into Candle Sockets and 1 E26 60Watt Bulb(not included) into Down Light Socket.
14. Power on and ENJOY!!!

