

## **IMPORTANT SAFETY INSTRUCTIONS**

- To avoid injury or damage, mount only on a surface that is sturdy.
- To avoid electric shock, make sure the electricity is turned off at the main circuit breaker panel. If you are replacing an existing fixture, turn off the following in order: fixture, wall switch, and main fuse or breaker box.


**Note: Some types of fuses must be unscrewed to shut the power off.**

- If you are unclear as to how to proceed, please consult a licensed electrician.

**UNPACK THE FIXTURE:** Check the contents of the box. Box should contain all items on the parts diagram.

## **INSTALLATION INSTRUCTIONS**

- 1.** Measure Canopy (D) height with measuring tape. Adjust Nipple (E) on Mounting Plate (A) to the height of measured Canopy (D) plus 1/4" to allow them to protrude through Canopy (D) during installation. Lock Nipple (E) in place with the hex nuts.
- 2.** Secure Mounting Plate (A) to the junction box (not included) using Mounting Screws (B) provided. Ensure Mounting Plate (A) is positioned with Nipple (E) pointing away from the junction box.
- 3.** Place Canopy (D) against the ceiling by inserting Nipple (E) through the appropriate hole located on Canopy (D). Adjust Nipple (E) and hex nuts until 1/4" of the threaded portion is visible. Remove Canopy (D) from ceiling and set it aside.  
**Note: If 1/4" of Nipple (E) is not visible, remove Canopy (D) and re-adjust Nipple (E) to proper length and lock it in place with the hex nuts.**
- 4** Using the wire graph below, connect the appropriate wires from the fixture to the corresponding wires in the electrical junction box (not included) and secure Wire Connectors (C).



- A.** Connect the ground wire (bare copper or green) from your fixture to the:
- 1) ground wire in the junction box, or
  - 2) ground screw in the junction box
- B.** Connect the BLACK house wire to fixture hot wire that corresponds to diagram (black, round & smooth, white/grey with tracer, brown/gold without tracer).
- C.** Connect the WHITE house wire to fixture neutral wire that corresponds to diagram (white, ribbed/ridged, white/grey without tracer, brown/gold with tracer).

5. Place all wires and Wire Connectors (C) back into the junction box.

6. Place Canopy (D) against the ceiling, ensuring Nipple (E) is protruding through the hole in Canopy (D). Secure the fixture in place to the Mounting Plate (A) with Cap Nut (G).

**Note: If fixture does not sit flush against the ceiling, remove fixture and readjust Nipple (E) and hex nuts.**

7. Install light bulbs (not included) into Sockets (K).

8. Position Shade (F) into Shade Holder (J).

9. Pull Springed Shade Holder (J) and lock Shade (F) in place.

Enjoy your new fixture!

## PARTS DIAGRAM

**HELPFUL TOOLS:** Safety Goggles, Screwdriver, Wire Cutter/Stripper, Ladder, Measuring Tape

