

DOWNLIGHT RETROFIT SQUARE

SMOOTH, BAFFLED TRIM
4"



SMOOTH



BAFFLED



SPECIFICATIONS

ELECTRICAL

MODEL	DESCRIPTION	POWER	INPUT VOLTS	DIMMABLE	EFFICACY (LPW)	FREQUENCY	LIFETIME	WATT REPLACEMENT
LR23007	LED/DL4/3000K/FL/ES/SQ	10	120V	YES	65.0	50-60Hz	50,000	60
LR23001	LED/DL4/4000K/FL/ES/SQ	10	120V	YES	67.0	50-60Hz	50,000	60
LR23009	LED/DL4/5000K/FL/ES/SQ	10	120V	YES	70.0	60Hz	50,000	60
LR24825	LED/DL4/2700K/FL/B/SQ	10	120V	YES	62	50-60Hz	50,000	60
LR24826	LED/DL4/3000K/ FL/B/SQ	10	120V	YES	65	60Hz	50,000	60
LR24828	LED/DL4/4000K/FL/B/SQ	10	120V	YES	67	50-60Hz	50,000	60
LR24829	LED/DL4/5000K/FL/B/SQ	10	120V	YES	70	60Hz	50,000	60

PHOTOMETRIC

MODEL	COLOR (CCT)	TEMP	LUMEN	FLOOD	CRI	CASE	COST/YR	BASE TYPE	FINISH
LR23007	3000K	SOFT WHITE	650	90°	80	12	\$ 1.20	E26 ADAPTER	SMOOTH
LR23001	4000K	COOL WHITE	670	90°	80	12	\$ 1.20	E26 ADAPTER	SMOOTH
LR23009	5000K	BRIGHT WHITE	700	90°	80	12	\$ 1.20	E26 ADAPTER	SMOOTH
LR24825	2700K	WARM WHITE	620	90°	90	12	\$ 1.20	E26 ADAPTER	BAFFLED
LR24826	3000K	SOFT WHITE	650	90°	90	12	\$ 1.20	E26 ADAPTER	BAFFLED
LR24828	4000K	COOL WHITE	670	90°	90	12	\$ 1.20	E26 ADAPTER	BAFFLED
LR24829	5000K	BRIGHT WHITE	700	90°	90	12	\$ 1.20	E26 ADAPTER	BAFFLED

GENERAL

DIAGRAM

