



Archer® | K-9394

48" x 48" alcove shower base, center drain

Features

- Low-threshold design for easy entry and exit
- Covered drain with removable cover
- Single threshold for alcove installation
- Coordinates with other products in the Archer collection



Available Colors/Finishes

Color tiles intended for reference only.

0	White
96	Biscuit
NY	Dune
95	Ice Grey



1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
7-30-2026 06:21 - US-CA

THE BOLD LOOK
OF **KOHLER**

Codes/Standards

CSA B45.5/IAPMO Z124
ASTM E162
ASTM E662

Technical Information

All product dimensions are nominal.

Drain Location:	Center
Drain Hole Diameter:	3-3/8" (86 mm)
Shower Ledge Minimum Flat:	2-5/8" (66 mm)
Minimum Floor Load:	20 lbs/ft ²
Weight:	54 lbs (24.5 kg)

Material

- Acrylic

Recommended Products/Accessories

K-9132 Round shower drain for use with plastic pipe, gasket included

K-706008-D3 43-5/8"-47-5/8" W x 74" H bypass shower door with 1/4"-thick Frosted glass

K-706008-L 44-11/16"-47-5/8" W x 74" H bypass shower door with 1/4"-thick Crystal Clear glass

K-706010-L 44-5/8"-47-5/8" W x 74" H sliding shower door with 3/8"-thick Crystal Clear glass

K-706011-L 44-5/8"-47-5/8" W x 82" H sliding shower door with 3/8"-thick Crystal Clear glass

K-706014-D3 44-5/8"-47-5/8" W x 74" H bypass shower door with 1/4"-thick Frosted glass

K-706014-L 44-5/8"-47-5/8" W x 74" H bypass shower door with 1/4"-thick Crystal Clear glass

K-706016-L 44-5/8"-47-5/8" W x 74" H sliding shower door with 3/8"-thick Crystal Clear glass

K-706017-L 44-5/8"-47-5/8" W x 82" H sliding shower door with 3/8"-thick Crystal Clear glass

K-23726 Drain treatment

K-23732 Tub & shower cleaner

Warranty

See website for detailed warranty information.

KOHLER® Plastic Baths and Shower Bases Lifetime Limited Warranty



Installation

- Center drain
-

Installation Notes

Install this product according to the installation instructions.

Measure your actual product for rough-in details.

Shimming may be required to level the fixture.

Shimming may be required between the stud frame and the fixture.

Stud opening tolerance is + 1/4" (6 mm), - 0" (0 mm).



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.

7-30-2026 06:21 - US-CA