

# LED Outdoor Wall Light

(Textured Black)

Project Name: \_\_\_\_\_  
Location: \_\_\_\_\_  
Type: \_\_\_\_\_  
Qty: \_\_\_\_\_  
Comments: \_\_\_\_\_



## Dimensions

|        |        |
|--------|--------|
| Height | 22.00" |
| Width  | 7.00"  |

## Ordering Information

|        |                |
|--------|----------------|
| Finish | Textured Black |
|        |                |
|        |                |

## Dimensions

|                                    |              |
|------------------------------------|--------------|
| Extension                          | 3.75"        |
| Height from center of Wall opening | 11.00"       |
| Base Backplate                     | 21.75 X 6.75 |
| Weight                             | 8.40 LBS     |

## Photometrics

|                       |        |
|-----------------------|--------|
| Kelvin Temperature    | 3000 K |
| Color Rendering Index | 90     |

## Specifications

|                      |             |
|----------------------|-------------|
| Material             | Aluminum    |
| Diffuser Description | White Glass |

## Electrical

|               |             |
|---------------|-------------|
| Dimmable      | Yes         |
| Voltage       | 120 V       |
| Input Voltage | Single(120) |

## Qualifications

|                    |             |
|--------------------|-------------|
| Safety Rated       | Wet         |
| Title 24           | Yes         |
| ADA Compliant      | Yes         |
| Expected Life Span | 40000 Hours |
| Warranty           |             |

## Primary Lamping

|                        |            |
|------------------------|------------|
| Light Source           | LED        |
| Lamp Included          | Integrated |
| # of Bulbs/LED Modules | 2          |
| Delivered Lumens       | 600        |
| Initial Lumens         | 1410       |
| Delivered Efficacy     | 30         |
| Dimming                | Yes        |

**Notes:**  
1) Information provided is subject to change without notice.  
All values are design or typical values when measured under laboratory conditions.  
2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.