

Installing your door knocker

TOOLS REQUIRED



View installation videos at www.michaelhealy.com/installation

1. Hold your door knocker in the desired position and mark the hole locations with a pencil.
2. Drill holes using a 3/32" drill bit about 1/2" deep. **DO NOT** drill the holes all the way through the door.*
3. Screw the mounting bracket onto your door using the enclosed screws. You may have to remove the door knocker from its mounting bracket to access the mounting holes. Remove the hinge screw then reattach the door knocker after the mounting bracket is screwed to your door.

* The Ring and Nantucket Basket designs require different mounting methods. Visit www.michaelhealy.com/installation.

Caring for your door knocker

The protective coating on your door knocker will last many years. You can extend the life of the coating by occasionally applying a car wax to your door knocker.

Your door knocker can be cleaned with a mild soap and water if needed. Do not use solvents, such as brass cleaners, as these can damage the protective coating.

If you have questions

If you have any questions regarding installation or other concerns about your door knocker **please contact Michael Healy Designs directly** rather than the company from which you purchased it. Call us at 1-800-995-0988 or email customerservice@michaelhealy.com. You can also chat with us on www.michaelhealy.com.

THANK YOU FOR CHOOSING A

Michael Healy®

UNIQUE DOOR KNOCKER™



SHOW US YOUR CURB APPEAL



#AdoreMyDoor
@MichaelHealyDesigns

