

MODEL: LHI-EMBER

SKU: LHI-EMBER-[LP/NG]-[FINISH]

LAVA HEAT ITALIA

The Ember Collapsable Patio Heater

ANS Z83.26-2007/CSA 2.37-2007 Gas-Fired Outdoor Infrared Patio Heaters ANS Z83.26a-2008/CSA 2.37a-2008 Gas-Fired Outdoor Infrared Patio Heaters



Certification

Height

Width (Diameter)

Weight

Rated Heat Input

Fuel

Gas Supply

Manifold

Ignition

Diameter of Injector

Safety Features

Gas Supply Pressure

CSA

70 in. (1.78 m)

20 in. (50.8 cm)

55 lbs. (24.9 kg)

36,000 BTU/hr

LP / NG

20 lbs. (9 kg) LP cylinder / fixed NG line

11" W.C. (28 cm)

Electronic, three-position knob







0.077 in. (1.9 mm)

Flame failure device, anti-tilt switch

Max. 250 PSI, min. 5 PSI

- Power Rating: 36,000 BTU
- Coverage Area: 6 ft. radius / 12 ft. diameter / 37.70 ft. circumference / 113 sq. ft.
- Consumption Rate: Up to 10 hours with 20 lb. propane tank (LP)
- Lifetime Frame / 3-Year Parts / 1-Year Burner Limited Warranty (parts only)
- Construction: Marine-grade 6061-T6 aluminum chassis, 430-grade stainless emitter, borosilicate glass; collapsible chassis
- CSA Certified • 500-hour ASTM B117 salt-spray tested
- Safety: Tilt Switch Auto-Shutoff, Flame Failure Device

CONTROLS



Lava Heat Italia reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to www.lavaheat.com USA

6-7-2026 - US/