

ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING:

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Should any difficulty be experienced, please consult a qualified electrician before installing.

Installation steps:

1. Attach the nipple-1 to the crossbar, and secure with a washer and a hex nut.
2. Attach the crossbar to the outlet box by using the 2 mounting screws upwards.
3. Attach the cover to the housing and then put the column onto the cover.
4. Secure the loop to the pipe tightly.
5. Thread the fixture wire and ground wire through the top loop, canopy, nipple, hex nut, washer and crossbar in order.
6. Secure the top loop to the nipple and clamp the other end of the chain link to the top loop.
7. Make wire connections:
 - Smooth wire(w/ marking) from light to black wire from power source.
 - Ribbed wire(w/o marking) from light to white wire from power source.
 - Attach the ground wire and house ground wire to cross bar with a ground screw.Carefully tuck wires back into the outlet box.
8. Secure the canopy to the crossbar with the top loop.
9. attach the glass shade to the socket and secure with socket ring.
10. Install bulbs(Please do not exceed the maximum capacity which is recommended on the package.)
15. Turn on the power at fuse or circuit box and enjoy it

