Gold Wire Lighted Lamppost



Illustrated assembly guide

MODEL JL-2264

Finished dimensions
Heights: 48 in

Keep the power disconnected while joining the frame and light connections. Use the supplied power source for your item.

Assembly photos show the silver JL-2794. The same assembly sequence applies to this gold variant.

Before you begin

Arrange the components on a clean surface. Lantern head, pole, base and attached LED cord connections.



Have scissors ready when zip ties are used. Cut only excess tie ends; keep scissors clear of the light wires.

Assembly sequence

Follow the numbered steps. Check each frame and cord connection before applying power.

1 Connect the base and pole cords



Pull the wire from the base. Join the two matching plugs, then gently tuck the excess wire inside.

2 Seat the pole



Insert the pole into the base and press firmly until secure. Keep the cord clear of the frame joint.

3 Connect the lantern head



Join the matching plugs at the top of the pole. Align the lantern head with the pole opening.

4 Fit and test the lantern



Slide the lantern head into the top of the pole. Check all connections and operate the power control to verify the lights.

Warranty?
Troubleshooting?

Scan the QR code for
instructions, support, & registration.

XProductSupport.com/product/JL-2264

Instructions, support & warranty

Scan the mini card or click below to:

Watch the instructional video
Create a support ticket
Register your item for warranty

XProductSupport.com/product/JL-2264