

# PENDANT LIGHT

## Assembly Instructions



### CAUTION

• Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.

• Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

### TOOLS REQUIRED



Ladder



Safety glasses



Electrical tape




Phillips screwdriver




Flat blade screwdriver




Pliers




Wire strippers




Fixture




Shade




Long Rods




Canopy



Mounting Unit



Mounting Screws



Wire Nuts




Cap Nuts

**\*PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE**

# PENDANT LIGHT Assembly Instructions


## STEP 1

Screw the rods to the fixture. Make sure to feed the branch wires of the fixture through the rods during assembly. Remove or add rods to adjust the height. Secure the shade to the fixture using the socket ring.



## STEP 2

Use the mounting screws to attach the mounting unit to the junction box



## STEP 3



Make the electrical connection from the junction box to the fixture. Connect the ground wire to the mounting unit using the preinstalled green ground screw. Then, connect the positive, negative and ground wires with the supplied wire nuts. Secure with electrical tape

Connect Clear, Brown, Gold or Black Parallel Wire without tracer (round & smooth) or Black Fixture Wire to:

Black or Red Supply Wire or Insulated Wire (other than green) with copper conductor.

Connect Clear, Brown, Gold or Black \*Parallel Wire with tracer (square & ridged) or White Fixture Wire to:

White Supply Wire or Insulated Wire (other than green) with silver conductor




# PENDANT LIGHT

## Assembly Instructions

---

### STEP 4

Place the canopy over the mounting unit and secure the fixture with the cap nuts



### STEP 5

Install bulb (not included)  
(TYPE A MAX 60W)

