

VINYL : PREMIUM VINYL ADHESIVE

An acrylic based pressure sensitive adhesive, formulated to be completely free from materials which would contribute towards plasticiser migration, allied to our Easi-Flo and Easi-Control actuator system which gives finger-tip control.



RECOMMENDED USE: **SPYDER VINYL** is ideal for bonding Vinyl or PVC floor coverings to a variety of substrates including concrete, wood, stone and most other hard surfaces.

IMPORTANT: Always read the Safety Data Sheet before use. An evaluation of the adhesive should always be carried out in application conditions before commercial use is undertaken, this should also include reference to ageing.

METHOD OF USE: Surface Preparation. All surfaces must be clean, dry, and free from dust, grease, and any loose material. If degreasing is necessary, a detergent/water treatment should be considered first. If this is not appropriate, a suitable solvent cleaner may be used. Always check the effects of degreasing solvents on plastics, rubber materials and painted surfaces. All traces of cleaning solvent must be allowed to evaporate before the adhesive is applied. Application and bonding. It is always best to coat both surfaces. Spray onto a clean, dry and dirt free surface from approximately 10" (25 cm). Spray two coats if surface is dusty. Apply floor covering to substrate whilst the adhesive is still tacky, press the floor covering into place starting at the centre and working outwards.

STORAGE: Store in a cool dry well ventilated area at between 10-30°C.

SHELF LIFE: One year from the date of manufacture.

MANUFACTURING STANDARD: ISO 9001:2015

TYPICAL CHARACTERISTICS

Physical appearance	Low viscosity liquid
Colour	Amber
Chemical Type	Acrylic
Solvent	Acetone
Viscosity Brookfield RVT 20rpm at 25° C [mPa.s]	Approx 60cps
Total solids content	Approx 20%
Relative Density	Approx 1.2



DISCLAIMER The Information provided herein, especially recommendations for the usage and the application of this products, is provided in good faith, and no liability on the part of AFT Aerosols Ltd is stated or implied. No employee of AFT Aerosols Ltd has the authority to waive or alter in any way the content of this document. Due to different materials used, as well as to varying working conditions, production techniques, and the requirements of the end users, all of which are beyond our control, we strongly recommend that thorough and extensive trials are carried out in order to test the suitability of our products with regard to the required processes and applications. This should also include an ageing test which should be applied to all substrates used. It is also the responsibility of the purchaser and end user of this product to ensure that all appropriate actions necessary for the protection of the environment, and for the health and safety of their employees are observed. This datasheet replaces all former versions.