

PRODUCT SPECIFICATIONS

Elkay Scrub/Handwash Wall Mount Faucet. Faucet has a flow rate of 2.2 GPM, and . Faucet requires 2 faucet holes.

Mounting Type:	Wall Mount
Handle Type:	2" Lever Handle
Deck Clearance:	5-3/8"
Spout Reach:	3-1/2"
Spout Height:	8"
Hole Drillings:	2
Valve Connection:	1/2"-14 NPSM
Flow Rate:	2.2 GPM
Faucet Hole Size (min):	1-1/8"
Faucet Hole Spread:	4
Spout Type:	Bubblers + Other




AMERICAN PRIDE. A LIFETIME TRADITION.
Like your family, the Elkay family has values and traditions that endure. For almost a century, Elkay has been a family-owned and operated company, providing thousands of jobs that support our families and communities.

Product Compliance: ADA & ICC A117.1
ASME A112.18.1/CSA B125.1
NSF 372 (lead free)
NSF 61



Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards.

[Clean and Care Manual \(PDF\)](#)
[Warranty \(PDF\)](#)



PART: _____ QTY: _____

PROJECT: _____

CONTACT: _____

DATE: _____

NOTES: _____

APPROVAL: _____

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.