




32 TRAY HORIZONTAL / 57 SQ. FT COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



99 Hour
Timer



30-90°
Precision
Thermostats



Glass
Observation
Window



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

32HCUDG SPECIFICATIONS

| | | | |
|-------------------------|---|--------------------------------|-----------------------------------|
| Max Power Usage | 3.75 kW (1.875 kW x 2 Zones) | Total Tray Area | 57 sq. ft |
| Avg Power Usage | 1.5 kW (750 W x 2 Zones) | Total Trays | 32 |
| Voltage / Frequency | 200-240V/50-60Hz | Tray Dimensions | 16" x 16" |
| Max Amperage | 15A | Space Between Trays | 1 2/5" |
| Safety Breaker Required | Single Phase/20A | Tray Mesh Spacing | 5/16" x 5/16" |
| Temperature Range | Ambient Mode, 85 - 195°F | Machine Weight | 113 lbs |
| Timer | 0 - 99hr | Product Dimensions (W x H x D) | 3' .5" x 2' 7.25" x 21.5" |
| Independent Zones | 2 | Features | Memory Function, Ambient Air Mode |
| Product Material | Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminum door handle; Tempered glass observation window; Control Panel with PVC finish. | | |