



SEMI-FLUSH INSTALLATION INSTRUCTIONS

1. Carefully remove the fixture out of the carton and check that all parts are included referring to the above illustration.
2. Install the tube (1) onto the coupling (2).
3. Install the tube (7) onto the socket (8).
4. Install the glass ornament (9) and rubber washer (11) onto the frame (10), securing with the ball nut (12).
5. Assemble the canopy (13) onto the nipple (6) and secure with the steel washer (14) and hex nut (15).
6. Fixture is ready for lamping and installation.
7. Refer to the additional installation instructions included with the product for wiring and installation.
8. Install proper bulbs (not included) into each socket referring to the markings and/or labels on the fixture for maximum wattage.
9. Restore power to the installation point and retain this sheet for future reference.

PENDANT INSTALLATION INSTRUCTIONS

1. Carefully remove the fixture out of the carton and check that all parts are included referring to the above illustration.
2. Install the tube (1) onto the coupling (2).
3. Assemble the tube (4) together using the nipple (3). Attach the bottom end of tube (4) onto the nipple (6) and the other end onto the loop (5). Install the tube (7) onto the socket (8).
4. Install the glass ornament (9) and rubber washer (11) onto the frame (10), securing with the ball nut (12).
5. Fixture is ready for lamping and installation.
6. Refer to the additional installation instructions included with the product for wiring and installation.
7. Install proper bulbs (not included) into each socket referring to the markings and/or labels on the fixture for maximum wattage.
8. Restore power to the installation point and retain this sheet for future reference.