



General Information

Material number	99046
Type	floor light
Product segment	Indoor
Theme	fabric-conzept
FSC®	FSC® Mix70% Hevea br FSC® C152762

Dimensions

Article Height (in mm)	1515
Article Length (in mm)	780
Net Weight (in kg)	4.15 Kilogram
Article Overhang (in mm)	120
Article Width (in mm)	220
Article Diameter (in mm)	380
Canopy Length (in mm)	335
Canopy Width (in mm)	54
Canopy Height (in mm)	36
Base Diameter (in mm)	250
Base Length (in mm)	180
Base Width (in mm)	180
Installation Depth (in mm)	26
Cutout (in mm)	205
Canopy Diameter (in mm)	105

Material & Colour

Enclosure Material	steel
Enclosure Colour	black
Glass/Shade Material	fabric
Glass/Shade Colour	black
Cable Colour	black

Functionality

Switch Type	foot-switch
Battery	No
Function	LED not replaceable
Battery Type	CR2032
Sensor Angle (in °)	120
Sensitivity min. (in lux)	30
Burning Time min. (in sec.)	5
Burning Time max. (in sec.)	15
Distance (in Meter)	6

Technical Information

Protection Degree	IP20
Protection Class	2
Mains Voltage	220-240V,50/60Hz
Operation Voltage	220-240V,50/60Hz
max. Wattage (1)	1X40W
Dimmable	No
Spannung	220-240V 50/60Hz
U out	46-70V
I out	300mA
Hz	100Hz

Illuminant 1

Illuminant Type (1)	E27
Illuminant incl. (1)	Exclusive
Socket Type (1)	E27

Illuminant 1

Socket Type (1)	LED
Illuminant Type (1)	LED
Illuminant incl. (1)	Inclusive
Kelvin Complete	4000K
Light colour Complete	WHITE
Nominal Lifetime (in h)	25000
Switching Cycles	15000
Energy efficiency class (EEI)	E
Dimmable	No
Info changeability□light source/driver	LED + driver can be exchanged by a specialist
Rated Lamp Power (0,1W precision)	36
Colour Tolerance (LED, SDCM)	<6
Lumen Complete	4000

Illuminant 1

Socket Type (1)	GU10
Illuminant Type (1)	GU10-LED
Illuminant incl. (1)	Inclusive
Energy efficiency class (EEI)	F
Info changeability□light source/driver	LED exchangeable by customers, no driver included

